	1 auger only (LP)				
	N82-270HD	N82-270HDX	N92-300HD	N92-300HDXTR	N100-340HDXTR
Recommended horsepower (HP PTO)	40 to 75	40 to 75	75 to 100	75 to 100	100 to 160
Cutting width	82''	82''	92"	92"	100''
Cutting height	38''	36''	42''	40,5''	44''
Impeller RPM	540	540	540	540	540
Impeller diameter	27 ½''	27 ½''	30"	30"	34"
Impeller depth	11	11	12"	12"	14 ¼"
Number of blades	4	4	5	5	5
Impeller shaft diameter	1 9/16"	1 9/16"	1 ¾"	2"	2''
Balanced impeller	Std	Std	Std	Std	Std
Drum center height	18 ¾''	18 ¾''	21 ¼''	21"	21"
Rotary drum	-	-	-	Std	Std
Chute rotation by hydraulic motor with valve (gear)	Std	Std	Std	Std	Std
Hydraulic deflector	Std	Std	Std	Std	Std
Manual deflector	Opt	Opt	Opt.	Opt.	Opt.
Cylinder for chute deflector	2" x 6"	2" x 6"	2 ½" x 8"	2 ½" x 8"	2 ½" x 8"
Semi-industrial chute (2 deflectors)	Std	Std	Std	Std	Std
Hydraulic telescopic chute	-	-	-	-	Opt.
Main auger diameter	19 ½''	25''	23"	30''	30''
Balanced auger	Std	Std	Std	Std	Std
Revesible carbon steel blade	Std	Std	Std	Std	Std
Reversible 450 steel blade	Opt.	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel blade	Opt.	Opt.	Opt.	Opt.	Opt.
Tivar blade	Opt.	Opt.	Opt.	Opt.	Opt.
Lateral blade	Opt.	Std	Opt.	Std	Std
Adjustable carbon steel skid shoes	Std	Std	Std	Std	Std
Adjustable 450 steel skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable stainless steel skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.
Hoses support	Std	Std	Std	Std	Std
Rear support	Std	Std	Std	Std	Std
Driving chain number	80	80	80	100	100
Number of safety bolts	2	2	2	3	3
Bearing ductile iron casing	Std	Std	Std	Std	Std
Shaft P.T.O. standard	T60	T60	T80	T80	T80
1 000 to 540 reducer box	-	-	Opt.	Opt.	Opt.
Adjustable hitch	Std	Std	Std	Std	Std
Hitch category (QH = quick hitch)	1, 1 QH, ,2	1, 1 QH, 2	2, QH	2, QH	2, QH
Approx. weight (lb) - 1 auger	1 175	1 340	1 790	2 500	2 969