H Series Industrial snowblowers	N102-340HTRSI	N102-342HTRI N110-342HTRI N120-342HTRI	N102-362HTRI N110-362HTRI N120-362HTRI	N102-402HTRI N110-402HTRI N120-402HTRI
Recommended horsepower (HP PTO)	100 to 200	125 to 225	175 to 350	250 to 350
Cutting width	102''	102'' / 110'' / 120''	102'' / 110'' / 120''	102'' / 110'' / 120''
Cutting height	48''	53''	55''	60''
Impeller RPM	540	540	540	540
Snowremoval capacity ton/hour (up to)	1 500	1 700	2 550	3 100
Removable rotary drum in 450 steel	Std	Std	Std	Std
Impeller Depth	14 ¼''	16''	16''	16''
Drum contour in 450 steel	Std ¼''	Std 3/8''	Std 3/8''	Std 3/8''
Drum center height	22 ½''	21 ¼ ''	22 ¼ ''	24 ¼ ''
Impeller shaft diameter	2''	2''	2 ½ ''	2 ½ ''
Impeller diameter	34''	34''	36''	40''
Number of blades	5	5	5	5
Impeller in 450 steel	Std	Std	Std	Std
Balanced impeller	Std	Std	Std	Std
Main auger diameter	30'' double ribbon	30'' double bolted ribbon	30'' double bolted ribbon	30'' double bolted ribbon
Upper auger diameter	-	16''	16''	20''
Balanced auger	Std	Std	Std	Std
Teeth in 450 steel on augers	Std	Std	Std	Std
Hydraulic chute rotation by hydraulic motor	Std	Std with reducer	Std with reducer	Std with reducer
Semi industrial chute (2 deflectors)	Opt	Opt.	Opt.	Opt.
Hydraulic telescopic chute	Opt	Opt	Opt	Opt
Telescopic chute – articulated deflectors	-	Opt	Opt	Opt
Chute on right – chute on left or on right	Right	Left	Left	Left
Hydraulic cylinder – deflector action	2 ½'' x 8''	2 ½'' x 8''	2 ½'' x 8''	2 ½'' x 8''
Lights support on telescopic chute (2)	Opt.	Opt	Opt	Opt
Reversible cutting edge in 450 steel	Std	Std	Std	Std
Fixed lateral blades	Std	Std in 450 steel	Std in 450 steel	Std in 450 steel
Hydraulic lateral blade in 450 steel	-	Opt	Opt	Opt
Removable lateral skid shoes in 450 steel	Std	Std	Std	Std
Adjustable wheels (2 x 2)	-	Std	Std	Std
Sidewalk chain diverter in 450 steel	-	1x Std / 1x opt.	1x Std / 1x opt.	1x Std / 1x opt.
Truck / Guardrail diverter in Tivar	-	1x Std	1x Std	1x Std
Driving chain	100	Renold 100 HV	Renold 100 HV	Renold 100 HV
Clutch on driving shaft	-	Std	Std	Std
Number of safety bolt	3	1 (PTO)	1 (PTO)	1 (PTO)
Bearing ductile iron casing	Std	Std	Std	Std
PTO Shaft	V80 or V90	V80 or V90	V90 or W2600 (clutch)	V90 or W2600 (clutch)
Reducer box 1 000 / 540 RPM	Opt	Std	Std	Std
Lubrication system on reducer box	-	Opt.	Std	Std
Hitch category (QH = Quick hitch)	2, 2 QH	2, 2 QH	2, 2 QH	3, 3 QH
Approx weight (lbs)	3 622	4 365 / 4 505 / 4 645	4 690 / 4 840 / 4 990	4 930 / 5 085 / 5 240

The weight includes the standard equipments and telescopic chute.
Prices and specifications are subject to change without notice.